



AWSOD95-5 Omni 890 -950 MHz Antenna Kit

- (1) 900 MHz, 5 dB, Omni Antenna with Mounting Bracket
- (1) Lightning Protector / Bulkhead 0-6 GHz / NF to NM
- (1) 400 Series Low Loss Antenna Cable Assembly 5' / NM to NM
- (1) COAX-SEAL Weatherproofing Tape, 1/2 in. x 5 ft. roll.



AWSOD95



AWSLL400-5-NM/NM



AWSLP



Specifications

Frequency: 890 - 950 MHz
Gain: 5 dBi
Impedance: 50 Ohm nominal
Max Power: 100 watts
3db beamwidth, Azimuth: 360
3db beamwidth, Elecvation: 36
Polorization: Vertical
VSWR: 1.5:1
Lightning Protection:
 External recommended
Material: UV Stabilized Fiberglass
Length Dimensions: 24"
 38.1 cm x 1.3 cm
Weight: 1.3 lbs (0.6 kg)
Mounting: Pole / Mast Mount
Connector: Integral Female N

Specifications

Frequency Range	0-6000 MHz
Insertion Loss	0.1 - 0.5dB
VSWR	1.5:1
DC Breakdown Voltage	230V +/- 20%
Impulse Discharge	N/A
Impedance	50 OHM
Insulation Resistance	10,000 OHM
Input Power	N/A
Operating Temperature	-33 ~ 70 Deg C
Weight	5.6 oz (159 g)
Dimensions (L x W x H)	2.56 x 0.79 x 1.34 in. (65 x 20 x 34 mm)

